

LW 8005-BI

Screen systems

| | |
|---------------------|---|
| BASS: | 2 x 15" speaker with 4" voice coil |
| MID: | 6 x 6" speaker with 1,46" voice coil |
| TREBLE: | 6 x 1" driver with 1" voice coil |
| HORN: | 6 x Isophasic ABS horns, 140° x 12° each. With pan/tilt adjustment. |
| POWER: | Bass system, 1400W AES/2800W Prg. 4 ohm. Medium/treble system 930W AES/1860W Prg. 4 ohm. |
| SENSITIVITY: | Complete assembly: SPL 135dB - SPL peak 138dB LF Unit: Sens. 101dB 1W/1m. Half space - SPL 132,5dB - SPL 135,5dB with musical criteria HMF unit: Sens. 101,5dB 1W/1m. Free field - SPL 130,3dB - SPL 133,3dB with musical criteria |
| FREQUENCY RESPONSE: | 28/22.000 Hz. For biamp cut off freq. please use our LW-8080 DSP Processor |
| SIZE: | 212,6 x 66 x 61,6 cm. |



A screen system including LAT2014 (Line Array Technology), which combines professional compression drivers with true isophasic horns to achieve an extreme -3dB coverage throughout the whole audience area. 2 x 15" bass section plus a middle-treble section with Line Array Technology and 6 x 6" medium drivers plus 6 x 1" compression drivers + 6 x isophasic horns. For the biamp cut off frequency, please use our LW-8080 DSP Processor, which is delivered with all necessary presets, or a single crossover working at 150Hz.

